

CLIMATE CHANGE IMPACTS AND ADAPTATION PILOT STUDY

HOWARD HANSON DAM

Green River, Washington

Kevin Shaffer, P.E.

Hydraulic Engineer

Seattle District

10 September 2014



®




**US Army Corps of Engineers
BUILDING STRONG®**



Climate Change & USACE




<http://corpsclimate.us/>



BUILDING STRONG®


Howard Hanson Dam



BUILDING STRONG®

Authorized Purposes

1. Flood Risk Management (October – February)
2. Fisheries Conservation (July – October)
3. Water Supply for City of Tacoma (July – October)



BUILDING STRONG®

Flooding Mechanisms in W. WA

- Virtually all major flooding caused by atmospheric rivers
- Storm orientation is key
- No significant spring snowmelt flooding



November 1959, Green River (King County Archives)





Neiman, P.J., L.J. Schick, F.M. Ralph, M. Hughes, G. A. Wick, 2011, Flooding in western Washington: The connection to atmospheric rivers, *Journal of Hydrometeorology*, 12, 1337-1358.



BUILDING STRONG®

Hydrologic Modeling

- ECHAM5 A1B GCM dynamically downscaled using the WRF model
- Hydrologic modeling with both the VIC model (macro scale) and the DHSVM (fine-scale)




BUILDING STRONG®

Unregulated Hydrology


Howard Hanson Dam

Auburn, Washington


VIC




VIC



DHSVM





DHSVM



BUILDING STRONG®

Flooding - Magnitude



Flood Flow = 12 kcfs



BUILDING STRONG®

Flooding - Timing

Spring

- DHSVM: more March floods
- VIC: no shift



Fall

- DHSVM: earlier fall floods
- VIC: more October floods




BUILDING STRONG®

Refill - Conservation




BUILDING STRONG®

Refill – M&I



BUILDING STRONG®

Adapted Refill – M&I



BUILDING STRONG®

Summary & Conclusions

- Higher winter flow, lower spring flow
- Resilient, but still wondering about AR changes
- Refill season compressed
- Potential adaptations for further study



BUILDING STRONG®

Questions?



BUILDING STRONG®




BUILDING STRONG®




BUILDING STRONG®

Green River Watershed



BUILDING STRONG®

February 1996




Atmospheric River



BUILDING STRONG®

Hydrologic Modeling

Flood statistics for Howard Hanson Dam inflow




VIC

DHSVM



BUILDING STRONG®

Reservoir Modeling




Three analysis categories: flooding, refill, and low flow




BUILDING STRONG®

Flooding – Spring Timing

DHSVM




VIC




BUILDING STRONG®

Flooding – Fall Timing

DHSVM



VIC



BUILDING STRONG®

Low Flow

- Models struggled with low flow calibration
- Two hydrologic models showed opposite trends:
 - ▶ VIC showed decrease in 7q10 flows
 - ▶ DHSVM showed increase
- In both simulations, the future time periods exhibited an increase in the number of days at minimum flow



BUILDING STRONG®